

Direct-Coupled Actuators

N05 Non Spring Return SmartAct Damper Actuators



Direct coupled actuators which provide modulating or floating control for air dampers, ventilation flaps, louvers and VAV units, and for mounting on ball valves.

Non spring return. Self centering shaft adaptor. For round shafts 8-16mm; square shafts 6-13mm. Declutch for manual operation. Switch selectable rotation direction. For dampers with an area of 1 square metre. 5 year warranty.

Voltage and Power	Control Mode	Torque (Nm)	Features	Part Number	Stock/Indent
24Vac 6VA	2 Position/Floating	5	Runtime 110s	CN6105A1011	S
24Vac 6VA	2 Position/Floating	5	Runtime 110s 2 Auxiliary Switches	N0524-SW2	AUS
230Vac 6VA	2 Position	5	Runtime max 110s	N05230-2POS	AUS
24Vac 6VA	Modulating 0/2-10Vdc Floating 2 Position	5	Runtime 90-110s 0-10Vdc Feedback signal	CN7505A2001	S
24Vac 6VA	Modulating 0/2-10Vdc Floating 2 Position	5	Runtime 90-110s 0-10Vdc Feedback signal 2 Auxiliary Switches	N05010-SW2	AUS

N10 Non Spring Return SmartAct Damper Actuators



Direct coupled actuators for modulating or floating control of air dampers, ventilation flaps, louvers and VAV units, and for mounting on ball valves.

Non spring return. Self centering shaft adaptor. For round shafts 8-16mm; square shafts 6-13mm. Declutch for manual operation. Switch selectable rotation direction. For dampers with an area of 2 square metres. 5 year warranty.

Voltage and Power	Control Mode	Torque (Nm)	Features	Part Number	Stock/Indent
24Vac 6VA	2 Position/Floating	10	Runtime 110s	CN6110A1003	AUS
24Vac 6VA	2 Position/Floating	10	Runtime 110s 2 Auxiliary Switches	CN6110A1021	AUS
230Vac 6VA	2 Position	10	Runtime max 140s	N10230-2POS	I
24Vac 6VA	Modulating 0/2-10Vdc Floating 2 Position	10	Runtime 90-110s 0-10Vdc Feedback signal	CN7510A2001	AUS
24Vac 6VA	Modulating 0/2-10Vdc Floating 2 Position	10	Runtime 90-110s 0-10Vdc Feedback signal 2 Auxiliary Switches	CN7510A2209	AUS